SHUK ENGINEERING DISTRIBUTORS LTD



Safety Data Sheet

LOCTITE 243 MEDIUM STRENGTH THREADLOCKER known as Loctite 243 10ML AU

Page 1 of 11

243 10ML

SDS No. : 316211 V001.1 Revision: 25.07.2017 printing date: 05.05.2022

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

LOCTITE 243 MEDIUM STRENGTH THREADLOCKER known as Loctite AU

Intended use:

Product name:

Threadlocker

Supplier: Henkel New Zealand Ltd 2 Allens Rd

Auckland, 2013 New Zealand

Phone: +64 (9) 272-6710

Emergency information:

24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture HSNO Classification:

6.4A Class 6 - Toxicity, Subclass 6.4 - Eye irritant, Hazard Classification A Class 6 - Toxicity, Subclass 6.5 - Sensitisation, Hazard Classification B Class 9 - Ecotoxicity, Subclass 9.1 - Aquatic, Hazard Classification B

GHS Classification:

Hazard Class Serious eye irritation Skin sensitizer Acute hazards to the aquatic environment Chronic hazards to the aquatic environment Hazard Category Category 2A Category 1 Category 2

Category 2

Hazard pictogram:



Signal word:

Hazard statement(s):	H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary Statement(s): Prevention:	 P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	 P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P363 Wash contaminated clothing before reuse. P391 Collect spillage.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description:	Mixture
Type of preparation:	Methacrylate resin based threadlocker

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Tetramethylene dimethacrylate	2082-81-7	10- < 30 %
2,4,6-Triallyloxy-1,3,5-triazine	101-37-1	1- < 10 %
Propane-1,2-diol	57-55-6	< 2 %
Maleic acid	110-16-7	< 1 %
Acetic acid, 2-phenylhydrazide	114-83-0	< 1 %
non hazardous ingredients~		60 %

SECTION 4 FIRST AID MEASURES

Ingestion:	Rinse mouth, do not induce vomiting, consult a doctor.
Skin:	Rinse with running water and soap. Seek medical advice.
Eyes:	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
First Aid facilities:	Eye wash Normal washroom facilities

Medical attention and special treatment:

Treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	If product is involved in fire extinguish with dry powder, foam or carbon dioxide.
Decomposition products in case of fire::	In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released. Irritating organic vapours.
Particular danger in case of fire::	None
S pecial protective equipment for fire-fighters:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Avoid skin and eye contact. Ensure adequate ventilation.
Environmental precautions:	Do not let product enter drains.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:	Use only in well-ventilated areas. Avoid skin and eye contact.
Conditions for safe storage:	Ensure good ventilation/extraction. Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to
	containers as contamination may reduce the shelf life of the bulk product.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
PARTICULATES NOT OTHERWISE CLASSIFIED, RESPIRABLE DUST 9002-88-4	Respirable dust.		3	-		-
PARTICULATES NOT OTHERWISE CLASSIFIED, INHALABLE DUST	Inhalable dust.		10	-	-	-
PROPANE-1,2-DIOL, PARTICULATESONLY 57-55-6	Particulate.		10	-	-	
PROPANE-1,2-DIOL, VAPOUR & PART ICULATES	Vapor and particulates.	150	474	-	-	-
CUMENE 98-82-8		-	-		75	375
CUMENE		25	125	-	-	-

Engineering controls:	Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.
Eye protection:	Wear protective glasses.
Skin protection:	Wear suitable protective clothing. The use of chemical resistant gloves such as Nitrile is recommended.
	Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
	The use of chemical resistant gloves such as Neoprene or Natural Rubber is recommended
Respiratory protection:	Use only in well-ventilated areas. If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Blue
	Liquid
Odor:	Characteristic
pH:	Not available.
Specific gravity:	1.09
Boiling point:	>149 °C (>300.2 °F)
Flash point:	>93 °C (>199.4 °F)
Vapor pressure:	< 300 mbar
(no method; 50 °C (122 °F))	
Density:	1.09 g/cm3
Solubility in water:	Slightly soluble
Viscosity (dynamic):	1,700 - 2,400 mPa.s
(Brookfield; Instrument: RVT;	
speed of rotation: 20 min-1;	

Spindle No: 3; Method: ;; LCT STM 10; Viscosity Brookfield) VOC content:

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid:	Keep away from heat, spark and flame.
Incompatible materials:	Strong acids and oxidizing agents. Oxy gen scavengers. Strong alkalis. Reducing agents. Other poly merization initiators.
Hazardous decomposition products:	In case of fire toxic gases can be released. Irritating vapors. Oxides of carbon.

SECTION 11 TOXICOLOGICAL INFORMATION

Health Effects:	
Ingestion:	May be harmful if swallowed.
Skin:	May cause skin irritation.
	May cause skin sensitization.
Eyes:	This product is irritating to the eyes.
Inhalation:	May cause respiratory tract irritation.
Aggrevated med. condition:	Eye, skin, and respiratory disorders.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time	_	
Tetramethylene dimethacrylate 2082-81-7	LD50	10,120 mg/kg	oral		rat	not specified
2,4,6-Triallyloxy-1,3,5-	LD50	753 mg/kg	oral		rat	OECD Guideline 401 (Acute
triazine	LD50	> 2,000 mg/kg			rabbit	Oral Toxicity)
101-37-1			dermal			OECD Guideline 402 (Acute Dermal Toxicity)
Propane-1,2-diol	LD50	22,000 mg/kg	oral		rat	not specified
57-55-6	LC0	317.042 mg/l	inhalation	2 h	rabbit	not specified
	LD50	> 2,000 mg/kg	dermal		rabbit	not specified
Maleic acid	LD50	708 mg/kg	oral		rat	not specified
110-16-7	LD50	1,560 mg/kg			rabbit	not specified
			dermal			

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Propane-1,2-diol 57-55-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Maleic acid 110-16-7	irritating	24 h	human	Patch Test

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Propane-1,2-diol 57-55-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Maleic acid 110-16-7	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Tetramethylene dimethacrylate 2082-81-7	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Propane-1,2-diol 57-55-6	not sensitising	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Maleic acid 110-16-7	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Maleic acid 110-16-7	sensitising	Mouse local lymphnod e assay (LLNA)	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Haz ardous components	Result	Type of study/	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Tetramethylene	negative	in vitro mammalian	with and without		OECD Guideline 476 (In vitro
dimethacrylate	negative	chromosome	with and without		Mammalian Cell Gene
2082-81-7	positive	aberration test	with and without		Mutation Test)
		bacterial reverse			OECD Guideline 471
		mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)
		in vitro mammalian			OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
		aberrationtest			Aberration Test)
Propane-1,2-diol	negative	bacterial reverse	without		Ames Test
57-55-6	negative	mutation assay (e.g	with and without		OECD Guideline 473 (In vitro
		Ames test)			Mammalian Chromosome
		in vitro mammalian			Aberration Test)
		chromosome			
		aberrationtest			
Propane-1,2-diol	negative	oral: gavage		rat	not specified
57-55-6	negative	intraperitoneal		mouse	not specified
	negative	oral: gavage		rat	not specified
Maleic acid	negative	bacterial reverse	no data		Ames Test
110-16-7	negative	mutation assay (e.g	with and without		OECD Guideline 476 (In vitro
		Ames test)			Mammalian Cell Gene
		mammalian cell			Mutation Test)
		gene mutation assay			

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Spe cies	Method
Propane-1,2-diol 57-55-6	NOAEL=1,700 mg/kg	oral: feed	2 yearsdaily	rat	not specified
Maleic acid 110-16-7	NOAEL=>= 40 mg/kg	oral: feed	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Do not empty into drains / surface water / ground water.

Ecotoxicity:

Toxic to aquatic life with long lasting effects.

Toxicity:

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time	-	
			Study			
Tetramethylene	LC50	32.5 mg/l	Fish	48 h		DIN 38412-15
dimethacrylate 2082-81-7						
Tetramethylene	EC50	9.79 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
dimethacrylate	EC30	9.79 mg/i	Algae	72 11	Desinodesinus subspicatus	201 (Alga, Growth
2082-81-7						Inhibition Test)
Tetramethylene	NOEC	2.11 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
dimethacrylate		-	_		_	201 (Alga, Growth
2082-81-7						Inhibition Test)
Tetramethylene	NOEC	20 mg/l	Bacteria	28 d	activated sludge, domestic	not specified
dimethacrylate						
2082-81-7 2,4,6-Triallyloxy-1,3,5-	LC50	4.36 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
triazine	LCJU	4.50 mg/i	1/1511	90 H	Oneoffighenus mykiss	203 (Fish, Acute
101-37-1						Toxicity Test)
2,4,6-Triallyloxy-1,3,5-	EC50	19.4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
triazine			-			202 (Daphnia sp.
101-37-1						Acute
						Immobilisation
2.4.6 Triallalana 1.2.5	EC0	5	Bacteria	3 h		Test) OECD Guideline
2,4,6-Triallyloxy-1,3,5- triazine	ECU	5 mg/l	Dacterra	5 11		209 (Activated
101-37-1						Sludge, Respiration
101 07 1						Inhibition Test)
Propane-1,2-diol	LC50	>10,000 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
57-55-6						
Propane-1,2-diol	EC50	34,400 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
57-55-6						202 (Daphnia sp. Acute
						Immobilisation
						Test)
Propane-1,2-diol	EC50	19,000 mg/l	Algae	14 d	Selenastrum capricornutum	OECD Guideline
57-55-6			_		(newname: Pseudokirchnerella	
					subcapitata)	Inhibition Test)
Propane-1,2-diol 57-55-6	NOEC	15,000 mg/l	Algae	14 d	Selenastrum capricornutum (newname: Pseudokirchnerella	OECD Guideline
57-55-0					subcapitata)	Inhibition Test)
Propane-1,2-diol	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	OECD Guideline
57-55-6	1000	> 1,000 mg1	Bueteriu	5 11	uetrvated sludge	209 (Activated
						Sludge, Respiration
						Inhibition Test)
Maleic acid	LC50	> 245 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
110-16-7 Maleic acid	EC50	42.91	Denhain	48 h	Dankais maana	OECD Guideline
110-16-7	EC30	42.81 mg/l	Daphnia	48 n	Daphnia magna	202 (Daphnia sp.
110 10 /						Acute
						Immobilisation
						Test)
Maleic acid	EC50	74.35 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	
110-16-7						201 (Alga, Growth
I	1 1		I	I	l	Inhibition Test)

Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

Page 9 of 11

SDS No.: 316211 V001.1

LOCTITE 243 MEDIUM STRENGTH THREADLOCKER known as Loctite 243 10ML AU

Tetramethylene	readily biodegradable	aerobic	84 %	OECD Guideline 310 (Ready
dimethacrylate				BiodegradabilityCO2 in Sealed
2082-81-7				Vessels (Headspace Test)
2,4,6-Triallyloxy-1,3,5-		aerobic	7 - 9 %	OECD Guideline 301 B (Ready
triazine				Biodegradability: CO2 Evolution
101-37-1				Test)
Propane-1,2-diol	not inherently	aerobic	60 %	OECD Guideline 302 B (Inherent
57-55-6	biodegradable			biodegradability: Zahn-
	_			Wellens/EMPA Test)
Propane-1,2-diol	readily biodegradable	aerobic	>70 %	OECD Guideline 301 A (new
57-55-6				version) (Ready Biodegradability:
				DOC Die Away Test)
Maleic acid	readily biodegradable	aerobic	97.08 %	OECD Guideline 301 B (Ready
110-16-7				Biodegradability: CO2 Evolution
				Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Tetramethylene dimethacrylate 2082-81-7	3.1					OECD Guideline 117 (Partition Coefficient (n- octanol / water), HPLC Method)
2,4,6-Triallyloxy-1,3,5- triazine 101-37-1	2.8				20 °C	not specified
Propane-1,2-diol 57-55-6	-1.07				20.5 °C	EU Method A.8 (Partition Coefficient)
Maleic acid 110-16-7	-1.3				20 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)
Acetic acid, 2- phenylhydrazide 114-83-0	0.74					not specified

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal of product:

Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

SECTION 14. TRANSPORT INFORMATION

Land Transport:

UN no.: Proper shipping name:

Class or division: Packing group:

Marine transport IMDG:

UN no.: Proper shipping name:

Class or division:

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide) 9 III

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide) 9

Packing group:	III
EmS:	F-A,S-F
Seawater pollutant:	Marine pollutant
Air transport IATA:	
UN no.:	3082
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Fatty acid amide)
Class or division:	9
Packing group:	III
Packing instructions (passenger)	964
Packing instructions (cargo)	964

Further information for transport:

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

SECTION 15. REGULATORY INFORMATION

HSNO Approval Number:	HSR002670
Site and Storage:	Refer to the site and storage requirements for this Group Standard. Refer to the HSNO controls for approved hazardous substances.
NZIoC:	Compliant for NZIOC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:	STEL - Short term exposure limit TWA - Time weighted average HSNO - Hazardous Substances and New Organisms GHS: Globally Harmonized System CAS: Chemical Abstracts Service LD 50: Lethal Dose 50%
	LC 50: Lethal Concentration 50% IMDG: International Maritime Dangerous Goods code IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
Reason for issue:	Reviewed SDS. Reissued with new date. involved chapters: 1 - 16
Date of previous issue:	29.01.2014
Disclaimer:	

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.