



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

PRODUCT NAME:

Intended use: Supplier: LOCTITE SI 595 CL known as LOCTITE 595 SF CL RTV 80ML EN Silicone sealant Henkel New Zealand Ltd 2 Allens Rd, Auckland, 2013 New Zealand Phone: +64 (9) 272-6710 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

Emergency information:

2. HAZARDOUS IDENTIFICATION

Not classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005. GHS Classification: No classification required.

3. COMPOSITION / INFORMATION ON INGREDIENTS

General chemical description: Mixture resins Type of preparation: Acetoxy curing silicone

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Silicon dioxide	7631-86-9	1- < 10 %
non hazardous ingredients~		60 %

4. FIRST AID MEASURES

	Do not induce vomiting.
INGESTION:	Have victim rinse mouth thoroughly with water.
	Seek medical advice.
	In case of contact, immediately remove contaminated clothing and flush skin with
SKIN:	copious amounts of water.
	Seek medical advice.





EYES:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
	Move to fresh air.
INHALATION:	Keep warm and in a quiet place.
	Seek medical advice.
FIRST AID FACILITIES:	Eye wash and safety shower. Normal washroom facilities.
MEDICAL ATTENTION	
AND SPECIAL TREATMENT:	Treat symptomatically.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:	Carbon dioxide, foam, powder.
DECOMPOSITION PRODUCT IN CASE OF FIRE:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen. Formaldehyde.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE- FIGHTERS:	Wear full protective clothing. Fire fighters should wear positive pressure self- contained breathing apparatus (SCBA).
ADDITIONAL FIRE FIGHTING ADVICE:	In case of fire, keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

	Avoid contact with skin and eyes.
PERSONAL PRECAUTIONS:	Ensure adequate ventilation.
	Wear protective equipment.
ENVIRONMENTAL PRECAUTIONS:	Do not let product enter drain
	Scrape up as much material as possible.
METHOD OF CLEANING:	Ensure adequate ventilation.
METHOD OF CLEANING.	Store in a partly filled, closed container until disposal.
	Dispose of contaminated material as waste according to Section 13.



Safety Data Sheet LOCTITE SI 595 CL known as LOCTITE 595 SF CL RTV

7. HANDLING & STORAGE

 HANDLING: Ensure that workrooms are adequately ventilated. Avoid contact with eyes, skin and clothing. Wear suitable protective clothing, safety glasses and gloves.
STORAGE: Keep container tightly sealed. Do not store or use near heat, spark, open flame or other sources of ignition. Store in a cool, well-ventilated place.

8. EXPOSURE CONTROL/ PERSONAL PROTECTION

Workplace exposure standards:

Ingredient [Regulated substance]	Form of	TWA	TWA	Ceiling	STEL	STEL
	exposure	(ppm)	(mg/m3)		(ppm)	(mg/m3)
Particulates not otherwise classified,	Inhalable		10			
inhalable dust Inhalable dust (not	dust.					
otherwise classified) 7631-86-9						
Particulates not otherwise classified,	Respirable		3			
respirable dust Respirable dust (not	dust.					
otherwise classified)						

BIOLOGICAL EXPOSURE LIMITS: None.

	Ensure adequate ventilation, especially in confined areas.
ENGINEERING CONTROLS:	Use local ventilation if general ventilation is insufficient to maintain vapor
	concentration below established exposure limits.
EYE PROTECTION:	For eye protection, use tightly fitted safety goggles and a face-shield.
SKIN PROTECTION:	Wear suitable protective clothing.
SKIN FROTECTION.	Protective gloves made of rubber.
RESPIRATORY PROTECTION:	If inhalation risk exists, wear a respirator or air supplied mask complying with
RESPIRATORY FROTECTION.	the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Translucent Paste	FLASH POINT:	> 93 °C
ODOUR:	Acetic acid	LOWER EXPLOSIVE LIMIT:	4 %(∨)
pH:	Not applicable	UPPER EXPLOSIVE LIMIT:	19.9 %(∨)
SPECIFIC GRAVITY:	1.1	VAPOUR PRESSURE:	< 13 mbar (20 °C)

SHUK.CO.NZ	
0800 735 000	
SALES@SHUK.CO.NZ	

All the above data are for guidance only and cannot be used to support any warranty claims due to application failure.





	vier than air 5 30 g/l	DENSITY:	1.01 g/cm3			
10. STABILITY & REACTIVITY						
STABILITY: CONDITIONS TO AVOID:	E Si	table under recommended storag xtremes of temperature. Humidity trong oxidizing agents.				
INCOMPATIBLE MATERIALS:	R	Polymerises in presence of water. Reaction with strong acids. Reaction with strong bases				
HAZARDOUS DECOMPOSITION F	RODUCTS: A (1	hermal decomposition can lead to and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen. At higher temperatures (>150C) mo traces).	ay release formaldehyde			
HAZARDOUS POLYMERIZATION:		Vill not occur.				

11. TOXICOLOGICAL INFORMATION

Health Effects:

Ingestion: May cause irritation of the stomach

Skin: May cause mild skin irritation.

Eyes: May cause mild irritation.

Inhalation: Inhalation of mist or spray may cause irritation of the respiratory tract and nasal passages.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Silicon dioxide 7631-86-9	LD50 LC50 LD50	>5,000 mg/kg > 2.08 mg/l > 5,000 mg/kg	oral inhalation dermal	4 h	Rat Rat Rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) not specified





Skin corrosion/irritation:

Hazardous components	Result	Exposure time	Species	Method
CAS-No.				
Silicon dioxide	Not irritating	4 h	Rabbit	OECD Guideline 404 (Acute
7631-86-9				Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure time	Species	Method
CAS-No.				
Silicon dioxide 7631-86-9	Not irritating	4 h	Rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Silicon dioxide 7631-86-9	negative negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay in vitro mammalian chromosome aberration test	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Silicon dioxide 7631-86-9	negative	Inhalation		Rat	Not specified

Repeated dose toxicity:

<u> </u>					
Hazardous components CAS-No.	Result	Route of application	Exposure time/ Frequency of treatment	Species	Method
Silicon dioxide 7631-86-9	NOAEL=> 4,000 - 4,500 mg/kg	Oral: feed	13 weeks daily	Rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents
Silicon dioxide 7631-86-9	NOAEL=1.3 mg/m3	Inhalation	13 w6 h/d, 5 d/w	Rat	equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)



Safety Data Sheet LOCTITE SI 595 CL known as LOCTITE 595 SF CL RTV

12. ECOLOGICAL INFORMATION

GENERAL ECOLOGICAL INFORMATION:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards., In the cured state contribution of this product to Environmental Hazards is insignificant in comparison to articles in which it is used., Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered. Do not empty into drains / surface water / ground water. Harmful to aquatic life.

ECOTOXICITY:

Toxicity:

Hazardous components CAS-No.	Value Type	Value Toxicity Study	Acute Toxicity	Exposure Time	Species	Method
Silicon dioxide 7631-86-9	LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Silicon dioxide 7631-86-9	EL50	> 1,000 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Silicon dioxide 7631-86-9	NOELR	10,000 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Algae, Growth Inhibition Test)
Silicon dioxide 7631-86-9	EL50	> 10,000 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Algae, Growth Inhibition Test)
Silicon dioxide 7631-86-9	EC0	10,000 mg/l	Bacteria	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)

Bioaccumulative potential / Mobility in soil:

Hazardous	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
Components		Factor (BCF)	Time			
CAS-No.						
Silicon dioxide 7631-86-9	0.53					QSAR (Quantitative Structure Activity Relationship)

SHUK.CO.NZ 0800 735 000 SALES@SHUK.CO.NZ

All the above data are for guidance only and cannot be used to support any warranty claims due to application failure.



Safety Data Sheet LOCTITE SI 595 CL known as LOCTITE 595 SF CL RTV

13. DISPOSAL CONSIDERATIONS

WATER DISPOSAL OF PRODUCT:

DISPOSAL FOR UNCLEANED PACKAGE:

Dispose of in accordance with local and national regulations After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Dispose of in accordance with local and national regulations.

14. TRANSPORT INFORMATION

Dangerous Goods information:

Land Transport: Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

Marine transport IMDG: Not dangerous goods

Air transport IATA: Not dangerous goods

15. REGULATORY INFORMATION

New Zealand regulatory information: Not classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

HSNO Approval Number: not applicable

SITE AND STORAGE:Refer to the site and storage requirements for this Group Standard. Refer to the
HSNO controls for approved hazardous substances.NZIOC:Compliant for NZIOC.



Safety Data Sheet LOCTITE SI 595 CL known as LOCTITE 595 SF CL RTV

16. OTHER INFORMATION

	STEL - Short term exposure limit
	TWA - Time weighted average
	HSNO - Hazardous Substances and New Organisms
	GHS: Globally Harmonized System
Abbreviations/acronyms:	CAS: Chemical Abstracts Service
	LD 50: Lethal Dose 50%
	LC 50: Lethal Concentration 50%
	IMDG: International Maritime Dangerous Goods code
	IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
Reason for issue: Date of previous issue:	Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1 - 16 25.07.2017
	23.07.2017

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material. The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's intended use. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

All the above data are for guidance only and cannot be used to support any warranty claims due to application failure.