

Technical Data Sheet

CHEMZ FG64

HI-LO GREASE

CMZ7264 (500ml)

High performance extreme pressure food grade lubricant

- Suitable for incidental food contact
- Reduces friction and wear in metal to metal and metal to plastic applications
- Operates at both low and high temperatures

CHEMZ FG64 can be used in variable retention tunnels, chillers and freezers -40°C

CHEMZ FG64 can be used in ovens and steriliser bearings +180°

CHEMZ FG64 excellent EP performance and resistant to water and corrosion

PERFORMANCE CHARACTERISTICS:

| | |
|---------------------------------|-------------------------------------|
| Appearance | Opaque light brown, viscous grease |
| Type of Film | Non-drying, water resistant film |
| Temperature Range, °C | - 40 to + 180 |
| Food Acids and Alkalis | Resistant to food acids and alkalis |
| Dropping Point, °C | > 300 |
| Four Ball — Weld load, kgf | 620 |
| Anti-rust Performance SKF-EMCOR | 0 - 0 |
| NLGI Grade | 1 - 2 |

AEROSOL PROPERTIES:

| | |
|------------------|-------------|
| Specific Gravity | 0.65 |
| Flash Point, °C | < 0 |
| Propellant | Hydrocarbon |

Storage/Shelf Life is 5 years if stored correctly

Empty aerosol container to be disposed of via metal scrap

