

Technical Data Sheet

CHEMZ Hi-Tac

CMZ7764 (400ml)

Heavy duty multi-purpose tacky lubricant

- Excellent anti-wear properties
- Resistant to steam and water
- Prevents corrosion in all weather
- Tacky adhesion qualities

Chemz Hi-Tac is a tacky multi-functional lubricant.

Chemz Hi-Tac is formulated to lubricate and protect exposed equipment.

Chemz Hi-Tac formulation is particularly suitable for gear and equipment in wet, steamy or humid conditions.

Chemz Hi-Tac applications covers all industrial, production and manufacturing applications including marine, transport, rural, construction and mining areas.

Chemz Hi-Tac is suitable for exposed equipment such as open gears turntables, slide rails, moving equipment, slides, chains, cables, belts, conveyers, machine slides and guides.

Technical
Information:

Appearance	Clear, light yellow viscous liquid
Solubility	Not soluble in water, resists washout
Steam Resistance	Good
Specific Gravity	0.80
Film Set-Up Time, seconds	15
Temperature Range, °C	-25 to +170
Flashpoint, °C (Residual Film)	> 200
Flashpoint, °C (Propellant)	< 0
Propellant	Hydrocarbon

MPI Approved C12 (All animal products except dairy)