

Gasseal

**Non Setting pipe sealant for metallic threaded joints
Primarily for Liquefied Petroleum Gases (LPG), Natural Gas, Air & Water**

Features

- Temperature range: -20°C to 125°C
- Suitable for low pressure 2.9 psi (0.2 bar) L.P.G. and natural gas
- Independently tested by BSI to BS EN 751-2 : 1997 Part 2 Class B for use with gas appliances and their auxiliary equipment
- Joints can be assembled and pressure tested immediately
- Non corrosive to aluminium, brass, copper, low carbon steel & zinc
- Resists vibration
- Compatible with foam forming leak testers
- Suitable for use by CORGI registered gas installers
- NOT SUITABLE FOR HIGH PRESSURE STORAGE INSTALLATIONS OR LPG IN LIQUID FORM
- MPI Approved C11

Directions for Use

- Do not apply in sub-zero temperatures
- Use on gas appliances and their auxiliary equipment only
- Not to be used on installation pipework
- Ensure surfaces are clean and free of contaminants. Apply with a brush
- The joints may be assembled and used immediately

Technical Data



Performance you can trust

Gasseal

Appearance	Off-white compound
Unworked penetration (IP50)	275 – 295
Base type	Castor oil
Solids	Inorganic thickener
Specifications	BS EN 751-2 : 1997 Part 2 Class B
BSI test parameters:	
Operating temperature range	-20 ⁰ C to 125 ⁰ C
Test pressure	0.2 bar (2.9 psi)
Suitable applications	LPG & Natural gas (gas appliances and their auxiliary equipment only) Air Water Steam
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack Sizes	300g