





# DENSO™ EXTERNAL CONCRETE JOINT SEALING SYSTEM

HIGH PERFORMANCE CONCRETE JOINT SEALING SYSTEM FOR THE PREVENTION OF BACKFILL INFILTRATION

SUITABLE FOR: Concrete pipes Culverts Crown units







## THE DENSO™ EXTERNAL CONCRETE JOINT SEALING SYSTEM

An external joint sealing system comprising a fast drying bitumen based primer, overwrapped by a tape constructed with a non-rotting synthetic carrier. The tape is impregnated with an adhesive mastic and backed on one side with a durable laminate. The adhesive mastic is protected with a siliconised release film which is removed during application.

#### **SYSTEM FEATURES:**

- Highly conformable sealing membrane prevents backfill infiltration
- Simple installation procedure
- Suits all component sizes
- Supersedes the requirement for outmoded mortar or banded joints
- Cold applied
- Tenacious adhesion
- Economical
- Accommodates joint deflection

#### **USES AND APPLICATION METHOD**

Suitable for sealing joints in concrete pipes, culverts and crown units to protect against the infiltration of backfill.

#### **Application Method**

- 1. Surface to be clean and dry.
- 2. Clean substrate and prime with Denso Primer D<sup>™</sup>. Then allow to dry.
- 3. Denso Bitumen Mastic to be used if the nominal gap between culverts >10mm.
- 4. Select the correct width of Premseal 450. Allow no less than 45mm overlap each side of joint.
- 5. Peel back about 0.5m of interleaving.
- Apply adhesive Premseal mastic face of tape to joint.
- 7. Pull tape taut to eliminate wrinkles and press into place.

### SECTIONAL VIEW OF STANDARD FLUSH JOINT CONCRETE PIPE

High tenacity polymer bitumen adhesive compound

Fast drying bitumen primer

Durable laminate tape resists damage by impact



www.shuk.co.nz



0800 735 000



office@shuk.co.nz

For any product inquiries please contact your closest branch.

**AUCKLAND** 09 838 8413

**NEW PLYMOUTH** 06 758 8300

**CHRISTCHURCH** 03 348 9445



