



Section 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Copper Anti-Seize Aerosol 400ml

Product Code: 7474

Uses: High temperature anti-seize lubricant aerosol

Company: Chemz Limited
Address: 80 Rangitane Place

Whakatu, Hastings

Telephone: +64 6 877 9690 Email: info@chemz.co.nz

Emergency Number 24 hr: 0800 764 766 (0800 POISON) National Poison Centre

Section 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ. Classified as a dangerous goods for transport purposes.

GHS Classifications:

Aerosol Category 2 Skin irritation Category 2 Eye irritation Category 2 Skin sensitisation Category 1

Germ cell mutagenicity Category 1

STOT - repeated exposure Category 2 (oral, inhalation)

STOT - single exposure Category 3

Hazardous to the aquatic environment chronic Category 2

HSNO Classifications:

2.1.2A	Flammable aerosol
6.3A	Irritating to the skin
6.4A	Irritating to the eye
6.5B	Contact sensitiser

6.6A Known or presumed human mutagen

6.9B Harmful to human target organs repeated exposure

6.9B Narcotic

9.1B Ecotoxic in the aquatic environment with long lasting effects

Pictograms







Signal Words: Danger

Hazard Statements

H222	Flammable aerosol
IIZZZ	FIGURIANIE GELUSUL

H229 Pressurised container: May burst if heated

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

H340 May cause genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure

H411 Toxic to aquatic life with long lasting effects.

Ref: Copper Antiseize Aero 7474 Date: 26.02.2023 Supersedes: 1.7.18 Issue No: 6 Page 1 of 6 pages



Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Paraffinic Mineral Oil, Highly Refined	64742-62-7	30 - 60
Heptanes	64742-49-0	10 - 30
Copper Powder	7440-50-8	10 - 30
LPG (butane, propane)	68476-85-7	30 - 60

Section 4 - FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE 0800 764 766 (0800 POISON) or doctor.

Ingestion: Not considered a normal route of entry. IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do

NOT induce vomiting. Where there is risk of vomiting, lean person forward or place on left side to avoid

aspiration of product into lungs. Obtain immediate medical attention.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice.

Skin contact: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.

Inhalation: IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.

Notes to physician: Treat symptomatically and supportively. No specific antidote.

Section 5 - FIRE-FIGHTING MEASURES

General fire hazards: Pressurised container, flammable aerosol.

Specific hazards: Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an

explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float and

be re-ignited on surface water.

Further advice: On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to

wear self-contained breathing apparatus if risk of exposure to products of combustion.

Extinguishing media: Use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective.

Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight streams of water.

Protective equipment: Firefighters must use standard protective equipment including flame retardant coat, helmet with face

shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Firefighting instructions: In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers

from fire area if you can do so without risk. Runoff can cause environmental damage.

Hazchem Code: 2YE

Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills: Spills will be extremely slippery. Clean up all spills immediately. Remove all sources of ignition. If safe to do,

damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation. Wash with water.

Major spills: Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage

from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent

(soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.

Ref: Copper Antiseize Aero 7474 Date: 26.02.2023 Supersedes: 1.7.18 Issue No: 6 Page 2 of 6 pages





Section 7 – HANDLING AND STORAGE

Handling Precautions: Read product label before use. Keep out of reach of children.

This product is highly flammable. Keep away from heat and open flames. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use. Beware:

Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.

Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry

place. Keep away from heat, sparks, and flame. Store locked up.

Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m ³	STEL, mg/m ³
Oil Mist, Mineral	5	10
Copper (respirable dust as Cu)	0.01	-
LPG (Liquefied petroleum gas – butane, propane)	1,800	-

Additional Information: Wash hands before eating, drinking and smoking.

Engineering Controls: No controls required when handling small quantities. Use with adequate ventilation.

Larger quantities: General exhaust is adequate under normal operating conditions. Exhaust ventilation should be designed to prevent accumulation and recirculation in the workplace. Ventilation equipment and

lighting should be explosion-resistant.

Protective Equipment: General protective gloves are recommended as product may cause an allergenic reaction. In an industrial

environment: chemical protective gloves, safety glasses or chemical goggles are recommended. Wash

contaminated clothing before reuse.

In case of inadequate ventilation, wear respiratory protection. If TWA is exceeded, wear an approved

respirator with a type A filter.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Copper coloured, liquid spray.

About 0.7

pH: Not applicable.

Vapour Density: > 1 (Air =1)

Vapour Pressure, kPa: 300 - 600

Boiling Point, °C: About 95

Melting Point, °C: Not applicable.

Flash Point, °C: < 0 (propellant)

Explosion Limit, % v/v: LEL 1.2% UEL 9.5%

Autoignition Temp, °C: > 250

Specific Gravity:

Solubility: Not soluble in water.

Section 10 - STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

Ref: Copper Antiseize Aero 7474 Date: 26.02.2023 Supersedes: 1.7.18 Issue No: 6 Page 3 of 6 pages





Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment: Information given is based on product testing, and/or similar products, and/or components.

Acute Oral Toxicity: LD₅₀ estimated to be> 5,000 mg/kg (based on component mixture).

Acute Dermal Toxicity: LD₅₀ estimated to be > 2,000 mg/kg (based on component mixture, excluding propellant).

Acute Inhalation Toxicity: LC₅₀ estimated to be > 20 mg/L, Rat 4 hour (based on component mixture). Inhalation of vapours may cause

drowsiness (narcotic) and dizziness.

Skin Irritation: May cause skin irritation. Prolonged/repeated contact may cause defatting of the skin and dermatitis. Avoid

contact with skin.

Eye Irritation: Spray is irritating to the eye. Expected to be reversible in 7 - 21 days.

Respiratory Irritation: Inhalation of vapours or mists may cause irritation to the respiratory system.

Sensitisation: Contains a contact sensitiser which may cause allergenic skin reaction in predisposed individuals.

Toxicological checks with similar products have not revealed any skin sensitivity aggravation. Not expected

to be a respiratory sensitiser.

Repeated Dose Toxicity: Prolonged contact with product may result in irritant contact dermatitis. Avoid skin contact.

Mutagenicity: Product is classified as mutagenic. Although there is no data on the mutagenicity of copper in humans, in vivo

studies and mammalian system in vitro studies suggest that copper is a potential human mutagen.

Carcinogenicity: Not expected to be carcinogenic.

Reproductive toxicity: Not expected to be toxic.

Additional Information: None of the components present in this material at concentrations equal to or greater than 0.1% are listed

by IARC, NTP, OSHA or ACGIH as being carcinogens.

Section 12 – ECOTOXICITY INFORMATION

Ecotoxicity: Slightly ecotoxic in the aquatic environment. No environmental hazard is anticipated with small volumes of

product, provided that it is handled and disposed of with due care and attention.

Mobility: Given its physical and chemical characteristics, the product has no soil mobility.

Persistence/degradability: Inherently biodegradable.

Bioaccumulation Potential: Bioaccumulation is unlikely.

Section 13 - DISPOSAL CONSIDERATIONS

Material Disposal: Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the

environment, in drains or in water courses.

Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of

pressurised aerosols in landfills. Incineration in an authorised facility is suggested.

Container Disposal: Recycle empty container if possible. Product containers are also considered wastes of the same class of the

contents and should be disposed of in accordance with applicable regulations.

Section 14 - TRANSPORT INFORMATION

Transport: Classified as a Dangerous Good for transport purposes.

Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7.

They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.

Proper Shipping Name: Aerosols
UN Number: 1950
Dangerous Goods Class: 2.1

Ref: Copper Antiseize Aero 7474 Date: 26.02.2023 Supersedes: 1.7.18 Issue No: 6 Page 4 of 6 pages





Transport Labels Required: Class 2 Flammable (Land, Sea and Air), EHSM (Sea and Air)

> Land, Sea, Air Sea, Air





Subsidiary Risk: Not applicable **Packing Group:** Not applicable

Marine Pollutant: Yes

EMS Number F-D, S-U (UN 1950 Flammable aerosols)

DG Segregation: This product is classified as a Dangerous Goods. Consult the Land Transport Rule: Dangerous Goods 2005,

and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

Section 15 - REGULATORY INFORMATION

Inventory Listing NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.

SDS regulations This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets)

Notice July 2017 (Amended April 2021).

EPA Approval Number: HSR002515 Aerosols (Flammable) Group Standard 2020. **EPA Hsno Controls:** Refer to www.epa.govt.nz for information on Controls.

This substance is to be managed using the conditions specified in an applicable Group Standard.

Section 16 - OTHER INFORMATION

Additional information

Personal Protective Equipment Guidelines: The recommendation for protective equipment contained is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and

apply control methods where appropriate.

Abbreviations CAS Chemical Abstract Service number

> **EMS** Emergency Response Procedures for Ships Carrying Dangerous Goods

EPA **Environmental Protection Agency** GHS Globally Harmonized System

IARC International Agency for Research on Cancer IATA International Air Transport Association **IMDG** International Maritime Dangerous Goods

Lethal Concentration, 50% / Median Lethal Concentration LC_{50}

 LD_{50} Lethal Dose, 50% / Median Lethal Dose

LEL Lower Explosion Limit mg/m³ Milligrams per Cubic Metre

NZIoC New Zealand Inventory of Chemicals

N.O.S. Not otherwise specified OFI Occupational Exposure Limit PEL Permissible Exposure Limit

Ref: Copper Antiseize Aero 7474 Date: 26.02.2023 Supersedes: 1.7.18 Issue No: 6 Page 5 of 6 pages



STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value
TWA Time Weighted Average
UEL Upper Explosion Limit

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of sds.

Ref: Copper Antiseize Aero 7474 Date: 26.02.2023 Supersedes: 1.7.18 Issue No: 6 Page 6 of 6 pages