



GHS Classifications:

SAFETY DATA SHEET

Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	FG24 Belt Grip Aerosol (Food Grade)
Product Code:	7224
Uses:	Food grade spray for indoor and outdoor transmission belts.
Company:	Chemz Limited
Address:	80 Rangitane Place
	Whakatu, Hastings
Telephone:	+64 6 877 9690
Email:	info@chemz.co.nz
Emergency Number 24 hr:	0800 764 766 (0800 POISON) National Poison Centre

Section 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ. Classified as a dangerous goods for transport purposes.

HSNO Classifications:

2.1.2A	Flammable aerosol	Flammable aerosol	Category 1
6.3A	Mildly irritating to the skin	Skin irritation	Category 2
6.9B	Harmful to human target organs or systems (narcotic)	STOT (repeated exposure)	Category 3
9.1B	Toxic to the aquatic environment with long lasting effects	Aquatic toxicity (chronic)	Category 2



Signal Words: Danger

Hazard Statements

- H222 Extremely flammable aerosol
- H315 Causes skin irritation
- H336 May cause drowsiness or dizziness
- H411 Toxic to aquatic life with long lasting effects

Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Hexanes	64742-49-0	30 - 60
Hydrocarbon propellant (LPG - Propane, Butane)	68476-85-7	30 - 60
Non Hazardous Ingredients		to 100

Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.





If exposed or if you feel unwell: Call a POISON CENTRE 0800 764 766 or doctor.

in exposed of it you reel units	ell Call a POISON CENTRE 0800 764 766 of doctor.
Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Ingestion:	IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain immediate medical attention.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.
Section 5 – FIRE-FIGHTING	B MEASURES
General fire hazards:	Pressurised container, extremely flammable aerosol.
Specific hazards:	Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float and be re-ignited on surface water.
Further advice:	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion.
Extinguishing media:	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.
	For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight streams of water.
Protective equipment:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting instructions:	In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.
Hazchem Code:	2YE
Section 6 – ACCIDENTAL R	RELEASE MEASURES
Minor spills:	Clean up all spills immediately. Remove all sources of ignition. If safe to do, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation.
Major spills:	Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.
Section 7 – HANDLING AN	ID STORAGE
Handling Precautions:	Read product label before use. Keep out of reach of children.
	This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use.
	Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.
Section 8 – EXPOSURE CO	NTROLS/PERSONAL PROTECTION

Exposure Limits:

No value assigned for product. Exposure standards for constituents (NZ WES);





	Material	TWA, mg/m ³	STEL, mg/m ³
	Hexanes	1,200	-
	LPG (Liquefied petroleum gas – butane, propane)	1,800	-
Additional Information:	Wash hands before eating, drinking and smoking.		
Engineering Controls:	No controls required when handling small quantities. Us	e with adequate ventilati	on.
	Larger quantities: General exhaust is adequate under no equipment and lighting should be explosion-resistant.	ormal operating condition	s. Ventilation
Protective Equipment:	Generally not required for small quantities. In an industrial environment: gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.		
	In case of inadequate ventilation wear respiratory prote respirator with a type A filter.	ction. If TWA is exceeded	, wear an approved

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear viscous liquid spray.
pH:	Not applicable.
Vapour Density:	> 1 (Air =1)
Vapour Pressure, kPa:	300 - 600
Boiling Point, °C:	About 60
Melting Point, °C:	Not applicable.
Specific Gravity:	About 0.7
Flash Point, °C:	< 0 (propellant)
Explosion Limit, % v/v:	LEL 1.2% UEL 9.5%
Autoignition Temp, °C:	443
Solubility:	Not soluble in water.

Section 10 – STABILITY AND REACTIVITY

Stability:

-

Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

Section 11 – TOXICOLOGICAL INFORMATION		
Basis for Assessment:	Information given is based on product testing, and/or similar products, and/or components.	
Acute Oral Toxicity:	Slight. LD_{50} estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).	
Acute Dermal Toxicity:	Not toxic. LD ₅₀ estimated to be > 3,200 mg/kg (based on component mixture, excluding propellant).	
Acute Inhalation Toxicity:	Not toxic. LC ₅₀ estimated to be > 20 mg/L, Rat 4 hour (based on component mixture). Inhalation of vapours may cause drowsiness (narcotic) and dizziness.	
	Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.	
Skin Irritation:	Prolonged/repeated contact may cause defatting of the skin and dermatitis.	
Eye Irritation:	Spray is irritating to the eye. Expected to be reversible in less than 7 days.	
Respiratory Irritation:	Inhalation of vapours or mists may cause irritation to the respiratory system.	
Sensitisation:	Not expected to be a sensitiser.	
Repeated Dose Toxicity:	Prolonged skin contact with product may result in irritant contact dermatitis.	





Additional Information:

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

Section 12 – ECOTOXICITY	INFORMATION
Ecotoxicity:	Ecotoxic in the aquatic environment with long lasting effects.
Mobility:	Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.
Persistence/degradability:	Expected to biodegrade.
Bioaccumulation Potential:	Expected to bioaccumulate.
Section 13 – DISPOSAL CO	NSIDERATIONS
Material Disposal:	Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
	Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.
Container Disposal:	Recycle empty container if possible or place in refuse waste stream. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.
Section 14 – TRANSPORT I	INFORMATION
Transport:	Classified as a Dangerous Good for transport purposes.
	Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.
Proper Shipping Name:	Aerosols
UN Number:	1950
Dangerous Goods Class:	2.1
Transport Labels Required:	Class 2 Flammable (Land, Sea and Air), EHSM (Sea and Air)
	Land, Sea, Air Sea, Air
Subsidiary Risk:	Not applicable
Packing Group:	Not applicable
Marine Pollutant:	Yes
EMS Number	F-D, S-U (UN 1950 Flammable aerosols)
DG Segregation:	This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

Section 15 – REGULATORY INFORMATION

EPA Approval Number:	HSR002515 Aerosols (Flammable) Group Standard 2017.
Inventory Listing	NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.
SDS regulations	This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.





EPA Hsno Controls:

Refer to <u>www.epa.govt.nz</u> for information on Controls. This substance is to be managed using the conditions specified in an applicable Group Standard.

Section 16 – OTHER INFORMATION Additional information Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate. Abbreviations AICS Australian Inventory of Chemical Substances ADG Australian Code for the Transport of Dangerous Goods by Road and Rail CAS **Chemical Abstract Service number** EMS Emergency Response Procedures for Ships Carrying Dangerous Goods EPA **Environmental Protection Agency** GHS **Globally Harmonized System** IARC International Agency for Research on Cancer IATA International Air Transport Association IMDG International Maritime Dangerous Goods Lethal Concentration, 50% / Median Lethal Concentration LC₅₀ Lethal Dose, 50% / Median Lethal Dose LD₅₀ LEL Lower Explosion Limit mg/m³ Milligrams per Cubic Metre NZIOC New Zealand Inventory of Chemicals N.O.S. Not otherwise specified OEL **Occupational Exposure Limit** PEL Permissible Exposure Limit STEL Short-Term Exposure Limit STOT-RE Specific target organ toxicity (repeated exposure) STOT-SE Specific target organ toxicity (single exposure) TLV Threshold Limit Value TWA Time Weighted Average UEL **Upper Explosion Limit**

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of msds.