



# Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: FG84 PTFE Dry Lube Aerosol (Food Grade) 400ml

Product Code: 7284

Uses: Dry Film PTFE Lubricant

Restrictions on Use: None identified

Company: Chemz Limited

Address: 80 Rangitane Place

Whakatu, Hastings

Telephone: +64 6 877 9690

Email: info@chemz.co.nz

Emergency Number 24 hr: 0800 764 766 (0800 POISON) National Poison Centre

## Section 2 – HAZARDS IDENTIFICATION

#### Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.

Classified as a dangerous goods for transport purposes.

# HSNO Classifications: GHS Classifications:

2.1.2A	Flammable aerosol	Flammable aerosol	Category 1
6.3B	Mildly irritating to the skin	Skin irritation	Category 3
6.4A	Irritating to the eye	Eye irritation	Category 2B



Signal Words: Danger

#### **Hazard Statements**

H222 Extremely flammable aerosol.
 H316 Causes mild skin irritation.
 H320 Causes eye irritation.

## Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
2-Propanol	67-63-0	10 - 30
Polytetrafluoroethylene	65530-85-0	1 - 10
Hydrocarbon propellant (LPG - Propane, Butane)	68476-85-7	> 60

Ref: FG84 PTFE Dry Lube 7284 Date: 3.7.19 Supersedes: 5.5.16 Issue No: 3 Page 1 of 5 pages





#### Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact: IF ON SKIN: Wash with plenty of soap and water. Direct contact may cause irritation in sensitive

individuals. If skin irritation occurs: Get medical advice/ attention.

Inhalation: IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.

**Ingestion:** IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Where there is

risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs.

Obtain immediate medical attention.

**Notes to physician:** Treat symptomatically and supportively. No specific antidote.

## Section 5 – FIRE-FIGHTING MEASURES

**General fire hazards** Pressurised, extremely flammable aerosol.

**Specific hazards:** Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an

explosive mixture with air. Vapours can travel to a source of ignition and flash back. May float and be re-

ignited on surface water. Will burn if involved in a fire.

Further advice: On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to

wear self-contained breathing apparatus if risk of exposure to products of combustion.

**Extinguishing media:** For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.

For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may

be ineffective. Do not discharge extinguishing waters into the aquatic environment.

Do NOT use straight streams of water.

**Protective equipment** Firefighters must use standard protective equipment including flame retardant coat, helmet with face

shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting instructions In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move

containers from fire area if you can do so without risk. Runoff can cause environmental damage.

Hazchem Code: 2YE

#### Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills: Clean up all spills immediately. Remove all sources of ignition. If safe, damaged cans should be placed in a

container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should

be gathered and stowed safely. Provide ventilation. Wash with water.

Major spills: Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent

spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.

Wash area down with excess water.

# Section 7 - HANDLING AND STORAGE

**Handling Precautions:** Read product label before use. Keep out of reach of children.

This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even

after use.

Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.

Ref: FG84 PTFE Dry Lube 7284 Date: 3.7.19 Supersedes: 5.5.16 Issue No: 3 Page 2 of 5 pages





Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool,

dry place. Keep away from heat, sparks, and flame. Store locked up.

## Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits:** No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m <sup>3</sup>	STEL, mg/m <sup>3</sup>
2-Propanol	983	1230
LPG (Liquefied petroleum gas – butane, propane)	1800	-

Additional Information: Wash hands before eating, drinking and smoking.

Engineering Controls: No controls required when handling small quantities. Use with adequate ventilation.

Larger quantities: General exhaust is adequate under normal operating conditions. Ventilation

equipment and lighting should be explosion-resistant.

**Protective Equipment:** Generally not required for small quantities. In an industrial environment: gloves, safety glasses or

chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work

clothing should not be allowed out of the workplace.

In case of inadequate ventilation wear respiratory protection. If TWA is exceeded, wear an approved

respirator with a type A filter.

## Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

**Physical state**: Clear liquid spray, dries to a white film

pH: Not applicable.

Vapour Density: > 1 (Air =1)

Vapour Pressure, kPa: 300 - 600

**Boiling Point, °C:** About 80

Melting Point, °C: Not applicable.

**Specific Gravity:** About 0.78

Flash Point, °C: < 0 (propellant)

Explosion Limit, % v/v: LEL 1.2% UEL 9.5%

Autoignition Temp, °C: Not applicable.

**Solubility:** Partially miscible in water.

## Section 10 - STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

#### Section 11 - TOXICOLOGICAL INFORMATION

Basis for Assessment: Information given is based on product testing, and/or similar products, and/or components.

Acute Oral Toxicity: LD<sub>50</sub> estimated to be 4,590 mg/kg (based on component mixture, excluding propellant). Acute Dermal Toxicity: LD<sub>50</sub> estimated to be > 5,000mg/kg (based on component mixture, excluding propellant).

**Acute Inhalation Toxicity:** LC<sub>50</sub> estimated to be about 285 mg/L, Rat 4 hour (based on component mixture).

Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.

**Skin Irritation:** May cause mild skin irritation. Prolonged/repeated contact may cause defatting of the skin which can

lead to dermatitis.

Ref: FG84 PTFE Dry Lube 7284 Date: 3.7.19 Supersedes: 5.5.16 Issue No: 3 Page 3 of 5 pages





Eye Irritation: Spray may be irritating to the eye. Expected to be reversible in less than 7 days.

Respiratory Irritation: Inhalation of vapours or mists may cause irritation to the respiratory system.

**Sensitisation:** Not expected to be a sensitiser.

Repeated Dose Toxicity: Prolonged contact with product may result in irritant contact dermatitis.

Additional Information: None of the components present in this material at concentrations equal to or greater than 0.1% are

listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

## Section 12 – ECOTOXICITY INFORMATION

**Ecotoxicity:** Not expected to be ecotoxic.

**Mobility:** Product is volatile and will rapidly evaporate to the air if released into water.

Persistence/degradability: More volatile components expected to degrade in air. Low persistence, expected to rapidly degrade in

environment and not expected to be bioaccumulative.

#### Section 13 - DISPOSAL CONSIDERATIONS

Material Disposal: Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the

environment, in drains or in water courses.

Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of

pressurised aerosols in landfills. Incineration in an authorised facility is suggested.

Container Disposal: Recycle empty container if possible. Product containers are also considered wastes of the same class of

the contents and should be disposed of in accordance with applicable regulations.

# Section 14 – TRANSPORT INFORMATION

**Transport:** Classified as a Dangerous Good for transport purposes.

Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7.

They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.

Proper Shipping Name: Aerosols
UN Number: 1950
Dangerous Goods Class: 2.1

Transport Labels Required: Class 2 Flammable



Subsidiary Risk: Not applicable

Packing Group: Not applicable

Marine Pollutant: No

**EMS Number** F-D, S-U

**DG Segregation:** This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous

Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

## Section 15 – REGULATORY INFORMATION

Inventory Listing NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.

SDS regulations This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data

Sheets) Notice July 2017.

Ref: FG84 PTFE Dry Lube 7284 Date: 3.7.19 Supersedes: 5.5.16 Issue No: 3 Page 4 of 5 pages





**Approved Handler:** 2.1.2A - Required for quantities greater than 3,000 litres (aggregate water capacity). **Location Test Certificate:** 2.1.2A - Required for quantities greater than 3,000 litres (aggregate water capacity).

**Tracking:** This substance is not a tracked substance.

EPA Approval Number: HSR002515 Aerosols (Flammable) Group Standard 2017.

EPA Hsno Controls: Refer to <a href="https://www.epa.govt.nz">www.epa.govt.nz</a> for information on Controls.

This substance is to be managed using the conditions specified in an applicable Group Standard.

# Section 16 - OTHER INFORMATION

Additional information Health Effects from Exposure: It should be noted that the effects from exposure to this product will

depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the

risks and apply control methods where appropriate.

Abbreviations AICS Australian Inventory of Chemical Substances

ADG Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Chemical Abstract Service number

EMS Emergency Response Procedures for Ships Carrying Dangerous Goods

EPA Environmental Protection Agency
GHS Globally Harmonized System

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC<sub>50</sub> Lethal Concentration, 50% / Median Lethal Concentration

LD<sub>50</sub> Lethal Dose, 50% / Median Lethal Dose

LEL Lower Explosion Limit
mg/m³ Milligrams per Cubic Metre

NZIoC New Zealand Inventory of Chemicals

N.O.S. Not otherwise specified
 OEL Occupational Exposure Limit
 PEL Permissible Exposure Limit
 STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value
TWA Time Weighted Average
UEL Upper Explosion Limit

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of msds.

Ref: FG84 PTFE Dry Lube 7284 Date: 3.7.19 Supersedes: 5.5.16 Issue No: 3 Page 5 of 5 pages