

**Safety Data Sheet**

Page 1 of 13

LOCTITE 567 TB250ML EN/CH/JP

SDS No. : 546886

V001.1

Revision: 31.08.2023

printing date: 23.01.2024

**SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

<b>Product name:</b>	LOCTITE 567 TB250ML EN/CH/JP
<b>Intended use:</b>	Adhesive/Sealant
<b>Supplier:</b>	Henkel New Zealand Ltd 2 Allens Rd Auckland, 2013 New Zealand Phone: +64 (9) 272-6710
<b>Emergency Telephone for Chemical Accidents:</b>	24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

**SECTION 2 HAZARDS IDENTIFICATION****Classification of the substance or mixture**

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

**GHS Classification:**

<b><u>Hazard Class</u></b>	<b><u>Hazard Category</u></b>	<b><u>Target organ</u></b>
Skin irritation	Category 2	
Serious eye irritation	Category 2A	
Skin sensitizer	Category 1	
Target Organ Systemic Toxicant - Single exposure	Category 3	respiratory tract irritation
Acute hazards to the aquatic environment	Category 2	
Chronic hazards to the aquatic environment	Category 3	

**Hazard pictogram:****Signal word:**

Warning

<b>Hazard statement(s):</b>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H401 Toxic to aquatic life. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary Statement(s):</b>	
<b>Prevention:</b>	P261 Avoid breathing mist/vapours. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.
<b>Storage:</b>	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
<b>Disposal:</b>	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

### SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

**General chemical description:** Mixture  
**Type of preparation:** Anaerobic Sealant

#### Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
3,3,5 Trimethylcyclohexyl methacrylate	7779-31-9	20- < 30 %
Ethene, homopolymer	9002-88-4	1- < 10 %
Titanium dioxide	13463-67-7	1- < 10 %
Silica, amorphous, fumed, cryst.-free	112945-52-5	1- < 10 %
Propane-1,2-diol	57-55-6	1- < 10 %
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	0.1- < 1 %
N,N-Diethyl-p-toluidine	613-48-9	0.1- < 1 %
N,N-dimethyl-o-toluidine	609-72-3	0.1- < 1 %
non hazardous ingredients~		30- <= 60 %

### SECTION 4 FIRST AID MEASURES

**Ingestion:** Rinse mouth, do not induce vomiting, consult a doctor.

**Skin:** Rinse with running water and soap.  
Seek medical advice.

<b>Eyes:</b>	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.
<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice.
<b>First Aid facilities:</b>	Eye wash Normal washroom facilities
<b>Medical attention and special treatment:</b>	Treat symptomatically and supportively.

## SECTION 5. FIRE FIGHTING MEASURES

<b>Suitable extinguishing media:</b>	Foam, extinguishing powder, carbon dioxide. Water spray or fog.
<b>Improper extinguishing media:</b>	High pressure waterjet
<b>Decomposition products in case of fire:</b>	Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide Carbon dioxide.
<b>Special protective equipment for fire-fighters:</b>	Wear full protective clothing. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).
<b>Additional fire fighting advice:</b>	In case of fire, keep containers cool with water spray.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions:</b>	Avoid skin and eye contact. Ensure adequate ventilation.
<b>Environmental precautions:</b>	Do not let product enter drains.
<b>Clean-up methods:</b>	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

## SECTION 7. HANDLING AND STORAGE

<b>Precautions for safe handling:</b>	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.
<b>Conditions for safe storage:</b>	Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Workplace exposure standards:**

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
PARTICULATES NOT OTHERWISE CLASSIFIED, RESPIRABLE DUST 9002-88-4	Respirable dust.		3	~	~	~
PARTICULATES NOT OTHERWISE CLASSIFIED, INHALABLE DUST	Inhalable dust.		10	~	~	~
TITANIUM DIOXIDE 13463-67-7			10	~	~	~
Particulates not otherwise classified, respirable dust Respirable dust (not otherwise classified) 112945-52-5	Respirable dust.		3	~	~	~
Particulates not otherwise classified, inhalable dust Inhalable dust (not otherwise classified)	Inhalable dust.		10	~	~	~
PROPANE-1,2-DIOL, PARTICULATES ONLY 57-55-6	Particulate.		10	~	~	~
PROPANE-1,2-DIOL, VAPOUR & PARTICULATES	Vapor and particulates.	150	474	~	~	~

**Biological Exposure Indices:**

None

**Engineering controls:**

Ensure good ventilation/suction at the workplace.

**Eye protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

Neoprene gloves.

Butyl rubber gloves.

Natural rubber gloves.

**Respiratory protection:**

If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES****Appearance:**

Off white

**Odor:**

paste

**pH:**

mild

**Melting point / freezing point:**

Not applicable, Product is non-polar/aprotic.

**Specific gravity:**

Not applicable, Product is a liquid

**Boiling point:**

1.15

&gt; 150 °C (&gt; 302 °F)

---

<b>Flash point:</b>	> 100 °C (> 212 °F)
<b>Vapor pressure:</b> (; 20 °C (68 °F))	< 0.30 mbar
<b>Vapor density:</b>	> 1
<b>Density:</b>	1.15 g/cm <sup>3</sup>
<b>Solubility in water:</b>	Insoluble
<b>VOC content:</b> (2010/75/EC)	< 3 %

## SECTION 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under recommended storage conditions.
<b>Conditions to avoid:</b>	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.
<b>Incompatible materials:</b>	Reacts with strong oxidants.
<b>Hazardous decomposition products:</b>	Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.  Toxic fluorine compounds. Ketones.

## SECTION 11 TOXICOLOGICAL INFORMATION

**Health Effects:****Ingestion:**

Ingestion may cause stomach ache and vomiting.

**Skin:**

Irritating to skin.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Eyes:**

Causes serious eye irritation.

Symptoms may include severe irritation, pain, tearing, blurred vision.

**Inhalation:**

This product is irritating to the respiratory system.

**Aggravated med.  
condition:**

Eye, skin, and respiratory disorders.

**Acute toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD0 LD50 LD0 LD50	> 5,000 mg/kg > 5,000 mg/kg > 2,000 mg/kg > 2,000 mg/kg	oral oral  dermal dermal		rat rat rat rat	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Ethene, homopolymer 9002-88-4	Acute toxicity estimate (ATE) Acute toxicity estimate (ATE) Acute toxicity estimate (ATE)	> 5,000 mg/kg > 5 mg/l > 5,000 mg/kg	oral inhalation dermal	4 h		Expert judgement Expert judgement Expert judgement
Titanium dioxide 13463-67-7	LD50 LC50 LD50	> 5,000 mg/kg > 6.82 mg/l > 10,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure) not specified not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	LD50 LC0 LD50	> 5,000 mg/kg 0.139 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) not specified OECD Guideline 402 (Acute Dermal Toxicity)
Propane-1,2-diol 57-55-6	LD50 LC50 LD50	22,000 mg/kg > 317.042 mg/l > 2,000 mg/kg	oral inhalation dermal	2 h	rat rabbit rabbit	not specified not specified not specified
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	LD50 LC50 Acute toxicity estimate (ATE)	382 mg/kg 1.370 mg/l 1,100 mg/kg	oral inhalation dermal	4 h	rat rat	other guideline: not specified Expert judgement
N,N-Diethyl-p-toluidine 613-48-9	Acute toxicity estimate (ATE) Acute toxicity estimate (ATE) Acute toxicity estimate (ATE)	100 mg/kg 3 mg/l 300 mg/kg	oral inhalation dermal			Expert judgement Expert judgement Expert judgement

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Silica, amorphous, fumed, cryst.-free 112945-52-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Propane-1,2-diol 57-55-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
N,N-Diethyl-p-toluidine 613-48-9	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethene, homopolymer 9002-88-4	not irritating	24 h	rabbit	FDA Guideline
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Silica, amorphous, fumed, cryst.-free 112945-52-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propane-1,2-diol 57-55-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Ethene, homopolymer 9002-88-4	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Propane-1,2-diol 57-55-6	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

<b>Hazardous components CAS-No.</b>	<b>Result</b>	<b>Type of study / Route of administration</b>	<b>Metabolic activation / Exposure time</b>	<b>Species</b>	<b>Method</b>
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethene, homopolymer 9002-88-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
Titanium dioxide 13463-67-7	negative negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay in vitro mammalian cell micronucleus test	with and without with and without with and without without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Titanium dioxide 13463-67-7	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Silica, amorphous, fumed, cryst.-free 112945-52-5	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro			not specified not specified not specified
Propane-1,2-diol 57-55-6	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	without with and without		Ames Test OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane-1,2-diol 57-55-6	negative negative negative	oral: gavage intraperitoneal oral: gavage		rat mouse rat	not specified not specified not specified
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	negative	dermal		mouse	not specified



**Repeated dose toxicity:**

<b>Hazardous components CAS-No.</b>	<b>Result</b>	<b>Route of application</b>	<b>Exposure time / Frequency of treatment</b>	<b>Species</b>	<b>Method</b>
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	NOAEL=1,000 mg/kg	oral: gavage	28 ddaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Titanium dioxide 13463-67-7	NOAEL=> 1,000 mg/kg	oral: gavage	92 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Propane-1,2-diol 57-55-6	NOAEL=1,700 mg/kg	oral: feed	2 yearsdaily	rat	not specified
Propane-1,2-diol 57-55-6	NOAEL=1000 mg/m3	inhalation	90 d6 h/d, 5 d/w	rat	not specified
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified

**SECTION 12. ECOLOGICAL INFORMATION****General ecological information:**

Do not empty into drains / surface water / ground water.

**Ecotoxicity:**

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

**Toxicity:**

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LC50	1.9 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	EC50	14.43 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	EC10	0.43 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethene, homopolymer 9002-88-4	LC50	> 100 mg/l	Fish	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethene, homopolymer 9002-88-4	EC0	> 1,000 mg/l	Bacteria	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	Fish	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	Bacteria	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshe- mm-Test)
Silica, amorphous, fumed, cryst.-free 112945-52-5	LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propane-1,2-diol 57-55-6	LC50	51,600 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propane-1,2-diol 57-55-6	EC50	18,340 mg/l	Daphnia	48 h	Ceriodaphnia dubia	other guideline:
Propane-1,2-diol 57-55-6	EC50	24,200 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propane-1,2-diol 57-55-6	NOEC	15,000 mg/l	Algae	14 d	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propane-1,2-diol 57-55-6	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	EC50	18.84 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	EC50	3.1 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	NOEC	1 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min			not specified
N,N-Diethyl-p-toluidine 613-48-9	LC50	42.25 mg/l	Fish	96 h	Danio rerio		OECD Guideline 203 (Fish, Acute Toxicity Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	35.2 mg/l	Daphnia	48 h	Daphnia magna		OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	7.42 mg/l	Algae	72 h	Desmodesmus subspicatus		OECD Guideline 201 (Alga, Growth Inhibition Test)
N,N-dimethyl-o-toluidine 609-72-3	LC 50	46 mg/l	Fish	96 h	Fathead minnow (Pimephales promelas)		

**Persistence and degradability:**

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	not readily biodegradable.	aerobic	16.8 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethene, homopolymer 9002-88-4	not readily biodegradable.	aerobic	1 %	ISO 10708 (BODIS-Test)
Propane-1,2-diol 57-55-6	readily biodegradable	aerobic	> 81.7 - 100 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	not readily biodegradable.	aerobic	3 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
N,N-Diethyl-p-toluidine 613-48-9	not readily biodegradable.	not specified	1 %	other guideline:
N,N-dimethyl-o-toluidine 609-72-3	not readily biodegradable.		1 %	other guideline:

**Bioaccumulative potential / Mobility in soil:**

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	5.25				20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Propane-1,2-diol 57-55-6	-1.07				20.5 °C	EU Method A.8 (Partition Coefficient)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	1.6				25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
N,N-Diethyl-p-toluidine 613-48-9	3.7					QSAR (Quantitative Structure Activity Relationship)

### SECTION 13. DISPOSAL CONSIDERATIONS

- Waste disposal of product:** Dispose of in accordance with local and national regulations.
- Disposal for uncleaned package:** After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

### SECTION 14. TRANSPORT INFORMATION

**Dangerous Goods information:**

**Land Transport:**

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

**Marine transport IMDG:**

Not dangerous goods

**Air transport IATA:**

Not dangerous goods

### SECTION 15. REGULATORY INFORMATION

**New Zealand regulatory information:**

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

**HSNO Approval Number:** Group standard HSR002670

**Site and Storage:** Refer to the site and storage requirements for this Group Standard.

**NZIoC:** Compliant for NZIoC

### SECTION 16. OTHER INFORMATION

**Abbreviations/acronyms:** IMDG: International Maritime Dangerous Goods code  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
GHS: Globally Harmonized System

**Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters: 1-16

---

**Date of previous issue:** 02.09.2018

**Disclaimer:**

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.