

Safety Data Sheet

Page 1 of 9

LOCTITE SF 790 AE18OZEN

SDS No. : 153698

V001.2

Revision: 15.12.2022

printing date: 18.01.2024

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name:	LOCTITE SF 790 AE18OZEN
Intended use:	Cleaner
Supplier:	Henkel New Zealand Ltd 2 Allens Rd Auckland, 2013 New Zealand Phone: +64 (9) 272-6710
Emergency information:	24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION**Classification of the substance or mixture****GHS Classification:**

Hazard Class	Hazard Category	Target organ
Aerosol	Category 2	
Skin irritation	Category 2	
Serious eye irritation	Category 2A	
Germ cell mutagenicity	Category 1B	
Carcinogenicity	Category 1A	
Target Organ Systemic Toxicant - Single exposure	Category 2	
Target Organ Systemic Toxicant - Single exposure	Category 3	Central nervous system
Acute hazards to the aquatic environment	Category 3	

Hazard pictogram:**Signal word:** Danger

Hazard statement(s):	H223 Flammable aerosol. H229 Pressurized container: May burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H340 May cause genetic defects. H350 May cause cancer. H371 May cause damage to organs. H402 Harmful to aquatic life.
Precautionary Statement(s):	
Prevention:	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe dusts or mists. P264 Wash hands thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
Disposal:	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
dichloromethane	75-09-2	70- < 90 %
Petroleum gases, liquified, sweetened	68476-86-8	20- < 30 %
methanol	67-56-1	3- < 10 %

SECTION 4 FIRST AID MEASURES

Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Get immediate medical attention.
Skin:	Immediately flush skin with plenty of water (using soap, if available). Seek medical advice.

Eyes:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Keep warm and in a quiet place. Seek medical advice.
First Aid facilities:	Eye wash and safety shower Normal washroom facilities
Medical attention and special treatment:	Treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Foam, dry chemical or carbon dioxide. Water Fog
Decomposition products in case of fire:	Thermal decomposition can lead to release of irritating gases and vapours. Irritating organic vapours. Phosgene. Hydrogen chloride. Oxides of carbon.
Particular danger in case of fire:	WARNING FLAMMABLE! Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Explosive rupture is possible.
Special protective equipment for fire-fighters:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Avoid contact with skin and eyes. Wear impervious gloves and chemical splash goggles. Avoid inhalation of vapor, fumes, dust and/or mist from the spilled material. See advice in section 8
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Wear appropriate personal protective equipment. Ventilate area. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Absorb the spilled material with an inert absorbent (nonflammable) material. Store in a closed container until ready for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:	Keep away from heat, spark and flame. Ensure adequate ventilation. Wear suitable protective clothing, safety glasses and gloves.
Conditions for safe storage:	Do not store or use near heat, spark, open flame or other sources of ignition. Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F). Store in a cool, dry place.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Workplace exposure standards:**

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
Dichloromethane(Methylene chloride) 75-09-2		50	174	-	-	-
Methyl alcohol (Methanol) 67-56-1		-	-	-	250	328
Methyl alcohol (Methanol)		200	262	-	-	-

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Methanol 67-56-1 [METHYL ALCOHOL]	Methyl alcohol	Urine	Sampling time: End of shift.	15 mg/l	NZ BEI		

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Dichloromethane 75-09-2	dichloromethane	Blood	Sampling time: End of shift.	1 mg/l	DE BAT		
Dichloromethane 75-09-2	Co-Hb	Blood	Sampling time: End of shift.	5 %	DE BAT		
Dichloromethane 75-09-2	dichloromethane	Blood	Sampling time period is immediately after exposure.	500 µg/l	DE BGW		
Methanol 67-56-1 [METHANOL]	methanol	Urine	Sampling time period is for long-term exposures, at the end of the shift after several preceding ones./ Sampling time period is at end of exposure or at end of shift.	15 mg/l	DE BGW		

Engineering controls: Use only in well ventilated areas.
Use local exhaust ventilation if the potential for airborne exposure exists.

Eye protection: For eye protection, use tightly fitted safety goggles and a face-shield

Skin protection: Wear protective equipment.
The use of polyvinyl alcohol (PVA) gloves is recommended.
Protective clothing that covers arms and legs.
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: grey, to, Off white
Aerosol

Odor: Sharp, Solvent

Specific gravity: 0.789

Flash point: < 5 °C (< 41 °F)

Lower explosive limit: 1.5 %(V)

Upper explosive limit: 9.5 %(V)

Solubility in water: Slightly soluble
VOC content: 30 % 237 g/l

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid: Heat, flames, sparks and other sources of ignition.

Incompatible materials: Strong oxidizing agents.
Potassium.
Strong alkalis.
Sodium.
Reactive metals.

Hazardous decomposition products: Thermal decomposition can lead to release of irritating gases and vapors.
Hydrogen chloride.
Oxides of carbon.
Irritating organic vapours.
Phosgene.

SECTION 11 TOXICOLOGICAL INFORMATION

Health Effects:

Ingestion: Harmful if swallowed.
Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin: This product is irritating to the skin.
Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes: Causes serious eye irritation.
Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Inhalation: Vapours may cause drowsiness and dizziness.
Inhalation of vapors may cause moderate to severe respiratory tract irritation.

Chronic effects: Studies on rodents have suggested that an ingredient in this product, when fed at high levels in the diet, may have cancer-causing potential.

Carcinogenicity: Category 1A (Carcinogen), May cause cancer.

Mutagenicity: Category 1B (Mutagen), This product contains an ingredient which has been associated with mutagenicity effects.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
dichloromethane 75-09-2	LD50 Acute toxicity estimate (ATE) LC50 LD50 Acute toxicity estimate (ATE)	> 2,000 mg/kg 2,500 mg/kg 86 mg/l > 2,000 mg/kg 2,500 mg/kg	oral oral inhalation dermal dermal	4 h	rat mouse rat	OECD Guideline 401 (Acute Oral Toxicity) Expert judgement not specified OECD Guideline 402 (Acute Dermal Toxicity) Expert judgement
methanol 67-56-1	Acute toxicity estimate (ATE)	300 mg/kg	oral			Expert judgement

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
dichloromethane 75-09-2	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
methanol 67-56-1	not irritating	20 h	rabbit	BASF Test

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
dichloromethane 75-09-2	irritating		rabbit	not specified
methanol 67-56-1	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
dichloromethane 75-09-2	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
methanol 67-56-1	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
dichloromethane 75-09-2	positive positive	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
dichloromethane 75-09-2	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
methanol 67-56-1	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian cell micronucleus test mammalian cell gene mutation assay	with and without without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) not specified equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
methanol 67-56-1	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
dichloromethane 75-09-2	NOAEL=6 mg/kg	oral: drinking water	104 wdaily	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
methanol 67-56-1	NOAEL=6.63 mg/l	inhalation: vapour	4 weeks 6 h/d, 5 d/w	rat	equivalent or similar to OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
methanol 67-56-1	NOAEL=0.13 mg/l	inhalation: vapour	12 m20 h/d	rat	equivalent or similar to OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

SECTION 12. ECOLOGICAL INFORMATION

General ecological information: Do not empty into drains / surface water / ground water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
dichloromethane 75-09-2	LC50	193 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
dichloromethane 75-09-2	NOEC	83 mg/l	Fish	28 d	Pimephales promelas	other guideline:
dichloromethane 75-09-2	EC50	27 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
dichloromethane 75-09-2	EC50	> 660 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
dichloromethane 75-09-2	EC50	2,590 mg/l	Bacteria	40 min	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
methanol 67-56-1	LC50	15,400 mg/l	Fish	96 h	Lepomis macrochirus	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
methanol 67-56-1	NOEC	7,900 mg/l	Fish	200 h	Oryzias latipes	OECD Guideline 210 (fish early life stage toxicity test)
methanol 67-56-1	EC50	18,260 mg/l	Daphnia	96 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
methanol 67-56-1	EC50	22,000 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
methanol 67-56-1	IC50	> 1,000 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
------------------------------	--------	----------------------	---------------	--------

dichloromethane 75-09-2	readily biodegradable	aerobic	68 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
methanol 67-56-1	readily biodegradable	aerobic	82 - 92 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
dichloromethane 75-09-2		2 - 40	42 d	Cyprinus carpio	25 °C	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
dichloromethane 75-09-2	1.25				20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
methanol 67-56-1		< 10	72 h	Leuciscus idus melanotus		not specified
methanol 67-56-1	-0.77					other guideline:

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal of product: Do not puncture or incinerate pressurized containers.
Dispose of according to regulations.

Disposal for uncleaned package: Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

Land Transport:

UN no.: 1950
Proper shipping name: AEROSOLS
Class or division: 2.1 (6.1)
Packing group:

Marine transport IMDG:

UN no.: 1950
Proper shipping name: AEROSOLS (Methylene chloride)
Class or division: 2.1 (6.1)
Packing group:
EmS: F-D ,S-U
Seawater pollutant: -

Air transport IATA:

UN no.: 1950
Proper shipping name: Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Class or division: 2.1 (6.1)
Packing group:
Packing instructions (passenger) 203
Packing instructions (cargo) 203

SECTION 15. REGULATORY INFORMATION

HSNO Approval Number: Group standard HSR002517

NZIoC: Compliant for NZIOC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms: TWA - Time weighted average
STEL - Short term exposure limit
IMDG: International Maritime Dangerous Goods code
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1-16

Date of previous issue: 17.11.2019

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.